



# KeyOrthoModel<sup>®</sup>


KeyOrthoModel is designed for high-speed and accurate prints.



ACCURATE



LOW SHRINKAGE



HIGH-SPEED

#4200003 (0.5kg bottle)

#4220003 (1kg bottle)

PROPERTY	METHOD	KEYORTHOMODEL
Flexural Strength	ASTM D790	79.6 MPa
Flexural Modulus	ASTM D790	2293 MPa
Tensile Strength	ASTM D638	51
Tensile Young's Modulus	ASTM D638	1850 MPa
Elongation at Break (%)	ASTM D638	5.60%
Shore Hardness	Scale D	86

## FEATURES

- OPTIMIZED TO PRINT @ 100 AND 200µm LAYER THICKNESS FOR HIGH THROUGHPUT
- PRINTS IN 1/2 THE TIME OF KEYMODEL AT SAME LAYER THICKNESS
- PAIRS WITH PRO-FORM<sup>®</sup>
- PERFECT FOR MAKING ALIGNERS
- WITHSTANDS THERMOFORMING TEMPERATURES



keystone<sup>®</sup>  
Industries

[keyprint.keystoneindustries.com](http://keyprint.keystoneindustries.com)

US: 480 South Democrat Road Gibbstown NJ, 08027  
EU: Keystone Industries GmbH Stockholzstr. 11 78224 Singen, Germany

US: 1.800.333.3131  
EU: +49 77 31 91 21 01

REV 0 05/2025